

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
Taiwan
Tel.: 886-2-8221-2567
Fax.: 886-2-2225-7268

Techfuse
PTC Devices
Resettable Fuse

PRODUCT: SMD0603-110
DOCUMENT: QR0429
ECN. NO.:
REV LETTER: A
REV DATE: 2011-3-29
PAGE NO.: 1 of 1

Specification Sheet


Terminal Pad Solderability:
Meets EIA Specification RS186-9E
And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification
0 = 110

**TABLE I. DIMENSIONS:**

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SMD0603-110	0	1.45	1.85	0.65	1.05	0.50	1.10	0.15

Unit:mm**TABLE II. PERFORMANCE RATINGS:**

Model	Marking	$V_{\max}$ (Vdc)	$I_{\max}$ (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{\min}}$ (Ω)	$R_{1_{\max}}$ (Ω)
SMD0603-110	0	6.0	40	1.10	2.20	0.50	8.0	0.10	0.040	0.280

Order Information**Packaging**

SMD0603		110		Tape & Reel Quantity	
Product name		Hold	Max	5,000 pcs/reel	
Size 1508 mm / 0603 mils		Current	voltage		
SMD: surface mount device		1.10A			

Recognition: UL Pending.