

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
Taiwan

Tel.: 886-2-8221-2567

Fax.: 886-2-2225-7268

Techfuse
PTC Devices
Resettable Fuse

PRODUCT: SMD1210-110

DOCUMENT: QR0429

ECN. NO.:

REV LETTER:

REV DATE: 2012-8-3

PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:

Meets EIA Specification RS186-9E

And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:

Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification

SMD1210-110 = α H




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SMD1210-110	α H	3.00	3.43	2.35	2.80	0.30	0.80	0.30

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SMD1210-110	α H	6	100	1.1	2.20	0.6	8	0.30	0.050	0.210

Order Information

Packaging

SMD1210	110	Tape & Reel Quantity	
Product name	Hold	Max	
Size 3225 mm / 1210 mils	Current	voltage	4500 pcs/reel
SMD: surface mount device	1.10A		

Recognition: UL Pending.