

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
Taiwan

Tel.: 886-2-8221-2567

Fax.: 886-2-2225-7268

Techfuse

PTC Devices

Resettable Fuse

PRODUCT: mSMD110

DOCUMENT: QR0429

ECN. NO.:

REV LETTER:

REV DATE: 2012-8-6

PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:

Meets EIA Specification RS186-9E

And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:

Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

α

Alpha Logo

110

Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
mSMD110	4.37	4.73	3.07	3.41	0.40	0.90	0.30	0.25

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	$V_{\max}$ (V)	$I_{\max}$ (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{\min}}$ (Ω)	$R_{1_{\max}}$ (Ω)
mSMD110	8.0	100	1.10	2.20	0.8	8.0	0.30	0.050	0.250

Order Information

Packaging

mSMD1812		110	Tape & Reel Quantity	
Product name	Size 4532 mm /1812 mils	Hold Current	Max voltage	1500 pcs/reel
SMD: surface mount device		1.10A		

Recognition: E201504/E319079

