

SEA&LAND ELECTRONIC CORP.

13F.,No.120-10,
Sec.3,Zhongshan Rd.,Zhonghe City,Taipei County,
Taiwan, R.O.C.
Tel.: 886-2-8221-2567
Fax.: 886-2-2225-7268

Techfuse
PTC Devices
Resettable Fuse

PRODUCT: R60-030
DOCUMENT: QR0429
ECN. NO.:
REV LETTER:
REV DATE: 2020/12/16
PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
meets UL94 V-0 Requirements

Lead-free,RoHS compliant

Lead Material:
Tin plated copper-clad steel, 24AWG (0.020"Dia)

Marking:

ChipFast Logo


R60 - Radial type 60V
030 - hold current
XXXY - Date code & Factory code




TABLE I. DIMENSIONS:

	A MAX	B MAX	C TYP	D MIN	E MAX	F MAX
mm	7.4	13.0	5.1	7.6	3.1	1.0
in	0.29	0.51	0.20	0.30	0.12	0.04

TABLE II. PERFORMANCE RATINGS:

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	R _{imin} (Ω)	R _{1max} (Ω)
R60-030	60	40	0.30	0.60	0.49	1.50	3.0	0.450	2.100

Order information

Packing

R60	030	K or S	R or U	Model	Reel Q'ty	Bag Q'ty
Radial type 60 V	Hold Current (A)	K=Kink leads S=Straight leads	R= Tape & Reel U= Bulk packaged	R60-030	3000	500

Tape & Reel packaging per EIA468-B stan

Recognition: UL/TÜV, approved.

E201504/E319079
R 50274672
2015/863/EU
EN14582

