

SEA&LAND ELECTRONIC CORP.

13F.,No.120-10,
Sec.3,Zhongshan Rd.,Zhonghe City,Taipei County,
Taiwan, R.O.C.

Tel.: 886-2-8221-2567
Fax.: 886-2-2225-7268

Techfuse
PTC Devices
Resettable Fuse

PRODUCT: R60-110
DOCUMENT: QR0429
ECN. NO.:
REV LETTER:
REV DATE: 2020/12/16
PAGE NO.: 1 of 1


Specification Sheet

Insulating Material:
meets UL94 V-0 Requirements

Lead-free,RoHS compliant

Lead Material:
Tin plated copper, 20AWG (0.032"Dia)

Marking:

- Sea&land Logo
-  R60 — Radial type 60V
- 110 — hold current
- XXXX — Date code & Factory code




TABLE I. DIMENSIONS:

	A	B	C	D	E	F
	MAX	MAX	TYP	MIN	MAX	MAX
mm	13.0	18.0	5.1	7.6	3.1	1.2
in	0.51	0.71	0.20	0.30	0.12	0.05

TABLE II. PERFORMANCE RATINGS:

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	R _{imin} (Ω)	R _{1max} (Ω)
R60-110	60	40	1.10	2.20	1.50	5.50	8.2	0.130	0.380

Order information

Packing

R60	110	K or S	R or U	Model	Reel Q'ty	Bag Q'ty
Radial type 60 V	Hold Current (A)	K=Kink leads S=Straight leads	R= Tape & Reel U= Bulk packaged	R60-110	1500	500

Tape & Reel packaging per EIA468-B standard.

Recognition: UL/TÜV, approved.

E201504/E319079
R 50274672
2015/863/EU
EN14582

