

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse


PRODUCT: R30-160
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2020/12/16
 PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
 meets UL94 V-0 Requirements
 Lead-free, RoHS Compliant

Lead Material:
 Tin plated copper-clad steel, 24AWG (0.020"Dia)

Marking:

- Sea&Land Logo
-  R30 - Radial type 30V
- 160 - hold current
- XXXY - Date code & Factory code




TABLE I. DIMENSIONS:

	A	B	C	D	E	F
	MAX	MAX	TYP	MIN	MAX	MAX
mm	8.9	15.2	5.1	7.6	3.0	1.2
in	0.35	0.60	0.20	0.30	0.12	0.05

TABLE II. PERFORMANCE RATINGS:

Model	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	R _{imin} (Ω)	R _{1max} (Ω)
R30-160	30	40	1.60	3.20	0.9	8.00	8.0	0.030	0.110

Order Information

Packing

R30	160	K or S	R or U	Model	Reel Q'ty	Bag Q'ty
Radial type 30 V (A)	Hold Current (A)	K=Kink leads S=Straight leads	R=Tape & reel U= Bulk packaged	R30-160	3000	500

Tape & Reel packaging per EIA468-B stan

Recognition: UL/TÜV, approved.

E201504/E319079
R 50274672
2015/863/EU
EN14582

