

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0603series
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2011-3-29
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification
 1 = 010




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.
SMD0603-010	1	1.45	1.85	0.65	1.05	0.40	1.00	0.15
SMD0603-020	2	1.45	1.85	0.65	1.05	0.40	1.00	0.15
SMD0603-025	2	1.45	1.85	0.65	1.05	0.40	1.00	0.15
SMD0603-035	3	1.45	1.85	0.65	1.05	0.40	1.00	0.15
SMD0603-050	5	1.45	1.85	0.65	1.05	0.50	1.10	0.15
SMD0603-075	7	1.45	1.85	0.65	1.05	0.50	1.10	0.15
SMD0603-100	0	1.45	1.85	0.65	1.05	0.50	1.10	0.15

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R _{i_min} (Ω)	R _{1_max} (Ω)
SMD0603-010	1	15.0	40	0.10	0.30	0.50	0.5	1.00	0.900	6.000
SMD0603-020	2	9.0	40	0.20	0.50	0.50	1.0	0.60	0.550	3.500
SMD0603-025	2	9.0	40	0.25	0.55	0.50	8.0	0.08	0.500	3.000
SMD0603-035	3	6.0	40	0.35	0.75	0.50	8.0	0.10	0.200	1.400
SMD0603-050	5	6.0	40	0.50	1.00	0.50	8.0	0.10	0.100	0.800
SMD0603-075	7	6.0	40	0.75	1.40	0.50	8.0	0.10	0.060	0.450
SMD0603-100	0	6.0	40	1.00	2.00	0.50	8.0	0.10	0.040	0.300

Order Information

Packaging

SMD0603		010		Tape & Reel Quantity	
Product name	Hold	Max			
Size 1508 mm / 0603 mils	Current	voltage	5,000 pcs/reel		
SMD: surface mount device	0.10A				

Recognition: UL Pending.